EVA-07S-SE / EVA-07S-SE RFID

Pro Earth (Single Phase)









Built in earthing arrangement means no costly groundwork, holes in driveways or additional mess or costly earth spike installation





STABLE

IP65 protection grade, capable for harsh environmental conditions



INTELLIGENT

Intelligent power adjustment, emergency stop, WiFi/APP/ethernet monitoring



TIME SHIFTING

You could save 100's per year by utilising off peak energy tariffs to charge your vehicle
















Input & Output


Input voltage 230V AC
Input frequency 50/60HZ
Output voltage 230V AC
Max. output power 7.3KW
Max. output current 32A

Charging interface type IEC 62196-2,Type 2



Protection

Over voltage protection Yes Under voltage protection Yes Over load protection Yes Short circuit protection Yes Yes Earth leakage protection Over-temp protection Yes Lightning protection Yes Earth loss disconnection Yes



Function and Accessory

Ethernet/WIFI/4G Yes/Yes/Opt
Connector Socket/Plug

LCD Opt

RCD Type A +6mA DC fault current protection

(Equivalent to Type B)

Emergency stop button Yes

Intelligent power adjustment Opt

RFID Yes (Only applies to EVA-07S-SE RFID)

Working environment

Protection degree IP65

Environment temperature -25°C~+50°C

Relative humidity 0-95%non-condensing

Cooling Natural air cooling

Standby power consumption <8W

Mechanical

Dimension (W/H/D) 240/380/145mm

Weight <7KG



Wall-mounting Yes

Ground-mounting pole Opt

Certification

Certificate CE

